



## Rurka WSG

**materiał:** włókno szklane pokryte silikonem

**temp. składowania:** 0°C do + 35°C

**temp. pracy:** -10°C do + 200°C

**palność:** UL-1441 VW-1

**wytrzymałość dielektryczna:** nominalna 1,5kV  
minimalna 1,0kV

**tolerancja:** ±5%

TYP	WYMIAR		OPAKOWANIE [m]	
	Ø [mm]	GRUBOŚĆ ŚCIANKI [mm]		
WSG-1,5-1	1,0	0,35	10	<input type="checkbox"/>
WSG-1,5-2	2,0	0,35	10	<input type="checkbox"/>
WSG-1,5-2,5	2,5	0,35	10	<input type="checkbox"/>
WSG-1,5-3	3,0	0,40	10	<input type="checkbox"/>
WSG-1,5-4	4,0	0,40	10	<input type="checkbox"/>
WSG-1,5-6	6,0	0,48	10	<input type="checkbox"/>
WSG-1,5-8	8,0	0,48	10	<input type="checkbox"/>
WSG-1,5-10	10,0	0,55	10	<input type="checkbox"/>
WSG-1,5-12	12,0	0,60	10	<input type="checkbox"/>

RoHS  
Compliant



złącz  
**TRYTYT.COM!**