

Everon® Copper Datacom U/UTP 200/24, Category 5e, LSZH/FRNC, Eca 4P, Green

CORNING

Part Number:
UU009120237

The Everon® Copper Datacom U/UTP 200/24 cable is designed up to 200MHz and its transmission characteristics exceed Category 5e specifications according to EN50288-3-1 IEC 61156-5. High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable. The cable has a streamlined construction and low weight. Unshielded cable (U/UTP).

Features and Benefits

U/UTP 200/24 cable designed up to 200 MHz

Fulfils all requirements of category 5e EN50288-3-1 and IEC 61156-5

Suitable for Classe D to Da according to ISO/IEC 11801. EN50173 and 1 Gigabit Ethernet according to IEEE 802.3an


Tested and approved for Power over Ethernet applications (PoE/PoE+) according to IEEE 802.3af, IEEE 802.3at

Low smoke and halogen-free (LSZH)

Unshielded cable (U/UTP)

Length marking on jacket

Eca



Everon® Copper Datacom U/UTP 200/24, Category 5e, LSZH/FRNC, Eca 4P, Green

CORNING

Specifications

General Specifications

Environment	Indoor
Category	5E
Cable type	U/UTP
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	Eca
Legacy Part Number	VOL5EUL4305
Brand	Everon®

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-3-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, TIA/EIA 568-C.2; IEC 60304
Design And Test Criteria	1000 Base-T IEEE 802.3 an; PoE / PoE++ IEEE 802.3af, IEEE 802.3at
Flame propagation test	IEC 60332-1
Smoke density	IEC 61034-2
Halogen content test	Zero Halogen to IEC 60754-1

Environmental Conditions

Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

Cable Design

Conductor	Copper Wire, AWG 24/1
Conductor insulation	Solid PE

Everon® Copper Datacom U/UTP 200/24, Category 5e, LSZH/FRNC, Eca 4P, Green

CORNING

Cable Design

Twisting	2 cores to a pair
Outer jacket material	LSZH/FRNC
Outer jacket colour	Green

Mechanical Characteristics

Fire load	330 MJ/km
Nominal outer diameter	4.9 mm
Min. bend radius installation	8x Cable-Ø
Maximum tensile strength	80 N

Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	534 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Surface transfer impedance	100 mΩ
Propagation velocity at >10 MHz (NVP*c)	66 %
Coupling attenuation	40 dB
Insulation Resistance	> 5000 MΩ*km

Dimensions

Width	305 m
Weight	289 kg

Everon® Copper Datacom U/UTP 200/24, Category 5e, LSZH/FRNC, Eca 4P, Green



Ordering Information

Product Number	UU009120237
Packaging method	Reelex Box
Units per delivery	1/1

Electrical Characteristics

Frequency [MHz]	4	10	20	63	100	200
Attenuation according to Standard [db/100m]	4.1	6.5	9.3	17.0	22.0	
Typical attenuation [db/100m]	3.8	6.0	8.5	15.2	19.5	28.0
NEXT according to Standard [db/100m]	56.3	50.3	45.8	38.4	35.3	
Typical NEXT Values [db/100m]	63.0	57.0	52.0	45.0	42.0	37.0
ACR-N according to Standard [db/100m]	52.2	43.8	36.5	21.4	13.3	
Typical ACR-N Values [db/100m]	59.2	51.0	43.5	29.8	22.5	9.0



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
 +00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2024 Corning Optical Communications. All rights reserved.