



product description: for position fixation of several pipes in one excavation
 distance spacers are for fixation 8 pipes and spacer can be split for fixation 2, 4 and 6 pipes

thermal resistance: -45 - +60 °C

meets the requirements: EN 61386-24:11, EN 61386-1 ed.2:09

storage: ČSN 64 0090



| item number | outer Ø pipe d (mm) | distance a (mm) | height b (mm) | fixing width h (mm) | fixing height k (mm) | material thickness tl. (mm) | total width l (8x) (mm) | total width after opening l (2x) (mm) | total width after opening l (4x) (mm) | total width after opening l (6x) (mm) |
|-------------------|---------------------|-----------------|---------------|---------------------|----------------------|-----------------------------|-------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| 07050/8_FB | 50 | 30 | 97 | 12 | 34 | 2,5 | 328 | 80 | 160 | 240 |
| 07063/8_FB | 63 | 30 | 116 | 12 | 43 | 2,5 | 381 | 95 | 190 | 280 |
| 07075/8_FB | 75 | 25 | 125 | 12 | 50 | 2,5 | 408 | 105 | 208 | 305 |
| 07090/8_FB | 90 | 28 | 148 | 14 | 60 | 2,5 | 482 | 125 | 247 | 360 |
| 07110/8_FB | 110 | 30 | 190 | 15 | 80 | 3 | 568 | 142 | 284 | 426 |
| 07125/8_FB | 125 | 38 | 210 | 20 | 88 | 3 | 658 | 175 | 336 | 497 |
| 07160/8_FB | 160 | 60 | 270 | 25 | 107 | 5 | 885 | 225 | 450 | 665 |
| 07200/8_FB | 200 | 80 | 345 | 25 | 133 | 5 | 1135 | 287 | 575 | 847 |

