



69dB

product description:

designed for distribution system with voltage 400 V and with maximum current 16 A
 designed for mounting into hollow walls (eg. walls of plasterboard)
 inlet openings made of flexible material
 marked inputs for sealing pipes in the flexible material (2x Ø16-20 mm, 2x Ø20-25 mm)
 air-tightness even with inserted pipe
 suitable for low energy and passive houses
 prevents airflow through the installation
 mounting screws with plastic foot are fitted with a twin self-tapping thread for quick installation
 instrument screws are tightened below the edge of the box
 extended edge situated for easy overlay installed device
 when mounting, it is not necessary to countersink the plasterboard edge
 possibility to insert screwless terminals
 when using box with the cover V 68HF, the IP protection is Ip30
 suitable for soundproof walls with maximum soundproofing $R_w = 69\text{dB}$
 for premises with increased need for protection of persons and property

material: PP (Pb-free, halogen-free)

color: grey (RAL 7035)

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

protection types: IP 30

weight: 23 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

KPL 64-50/LD HF_NA - boxes fitted with screws for mounting into double wall and device screws - package: 110 pcs boxes loose in cardboard

accessories: cover V 68HF
 screwless terminal plates TYP015, TYP016, TYP017, TYP018

auxiliary tools: saw-drill VPT 64
 universal carrier VPTU