

Ana-Quick polyamide conduit

PP MOD DUO BLACK



LIGHT DUO MODEL, FOR LIGHT MECHANICAL STRENGTH

The DUO PP-MOD is applicable for circumstances where intermediate repair is expected. Also for repair afterwards or when wires or cables have to be replaced type DUO PP-MOD is a perfect solution. Another feature of type DUO PP-MOD is the fact that the standard Ana-Quick Profi fittings can be used. Type DUO PP-MOD is used in the automotive industry and the transportation area.

Material & Construction:

Construction: Corrugated conduit from modified polypropylene PP, in slitted duo execution.

Flame properties: Class V2, according UL-94, flame-retarding.

Resistant against: Alcohol, greases, fuels, mineral oils, weak bases and weak acids.

Temperature: -40°C till +135°C, intermittent up to +150°C.

Colour: Black.

Classification according to NEN-EN-IEC 61386:

Compression resistance: Class 2, Light (320 N).

Impact resistance: Class 2, Light (1 J).

Tensile strength: Class 2, Light (250 N).

Protection class: IP 54.



Normal profile "double wall"

ANA-QUICK		DIAMETRE		BENDING RADIUS (CL)		STANDARD CARTON		SMALL CARTON		REEL		WEIGHT
Size (dn)	Inside (mm)	Outside (mm)	Static (mm)	Dynamic (mm)	Metre	Article No. black	Metre	Article No. black	Metre	Article No. black	(kg/m)	
7,5	5,6	10,3	25	45	50	802.207.0	-	-	-	-	0,02	
10	8,5	13,3	28	90	50	802.210.0	-	-	-	-	0,028	
13	11	16	35	135	50	802.213.0	-	-	-	-	0,037	
16	13	18,9	40	180	50	802.216.0	-	-	-	-	0,051	
17	15,1	21,3	45	210	50	802.217.0	-	-	-	-	0,056	
22	19,6	25,4	55	230	50	802.222.0	-	-	-	-	0,07	
23	21,6	28,1	60	240	50	802.223.0	-	-	-	-	0,09	
26	24	31,5	65	270	25	802.226.0	-	-	-	-	0,106	
29	26,6	34,4	100	300	25	802.229.0	-	-	-	-	0,128	
37	31,8	42,7	120	360	25	802.236.0	-	-	-	-	0,15	
50	43,9	53,9	140	420	25	802.248.0	-	-	-	-	0,225	

The fittings for Ana-Quick Profi are outlined in this chapter on pages 9 - 13 till 9 - 25

ANA-QUICK	7,5	10	12	17	23	29	37	50
ISO	M12	M12 - M16	M16 - M20	M20 - M25	M25	M32	M40	M50 - M63
PG	7	7 - 9 - 11	11 - 13,5	13,5 - 16	21	29	36	48
NPT	-	-	-	-	-	-	-	-