



Nr kat.	Kolor	Typ	Przyłączalność znamionowa	Natężenie prądu	Napięcie znamionowy	Materiał	Klasa ochronności	Wymiary [mm] A/B/C	Opak. zbiorcze	Uwagi
E.4031	biały 	PS 2,5mm <sup>2</sup>	0,75 - 2,5mm <sup>2</sup>	24A	400V	PE/PP	II	93/17/13	10	Temperatura pracy: -20°C do +80°C
E.4032		PS 4mm <sup>2</sup>	1 - 4mm <sup>2</sup>	32A				115/19/16		
E.4033		PS 6mm <sup>2</sup>	1 - 6mm <sup>2</sup>	41A				129/21/17		
E.4034		PS 10 mm <sup>2</sup>	1 - 10mm <sup>2</sup>	57A				138/23/19		
E.4035		PS 16 mm <sup>2</sup>	2,5 - 16mm <sup>2</sup>	76A				143/26/20		
E.4072		PS 25 mm <sup>2</sup>	2,5 - 25mm <sup>2</sup>	101A				186/29/25		
E.4031P	pomarańczowy 	PS 2,5mm <sup>2</sup>	0,75 - 2,5mm <sup>2</sup>	24A	400V	PE/PP	II	93/17/13	10	Temperatura pracy: -20°C do +80°C
E.4032P		PS 4mm <sup>2</sup>	1 - 4mm <sup>2</sup>	32A				115/19/16		
E.4033P		PS 6mm <sup>2</sup>	1 - 6mm <sup>2</sup>	41A				129/21/17		
E.4034P		PS 10 mm <sup>2</sup>	1 - 10mm <sup>2</sup>	57A				138/23/19		
E.4035P		PS 16 mm <sup>2</sup>	2,5 - 16mm <sup>2</sup>	76A				143/26/20		
E.4036P		PS 25 mm <sup>2</sup>	2,5 - 25mm <sup>2</sup>	101A				186/29/25		

