


UC900 HS23 Cat.7

S/FTP AWG23/1



Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T
IEEE 802.5 16 MB; ISDN; TPDDI; ATM
Power over Ethernet (PoE) / Type 1-4

Standards

EN 50173-1; EN 50288-4-1
ISO/IEC 11801; IEC 61156-5
IEEE 802.3af / at / bt

Flame resistance

EN50399: Class Eca
LSHF (LSOH): IEC 60332-1; IEC 60754-2; IEC 61034;

Construction

Conductor	bare copper wire, Ø 0.56 mm (AWG 23)	
Insulation	Foamskin PE, Ø 1.38 mm	
Twisting	2 cores to the pair	
Pair screen	Al-laminated plastic foil	
Cable lay up	4 pairs (PiMF) to the core	
Screen	copper braid, tinned	
Sheath	LSHF, orange	

Mechanical properties

Bending radius	without load	4 x D
	with load	8 x D
Temperature range	during operation	-20°C to + 60°C
	during installation	0°C to + 50°C

UC900 HS23 Cat.7

Electrical properties

at 20°C ± 5°C

Loop resistance		154 Ω/km	
Resistance unbalance		≤ 2%	
Insulation resistance	(500 V)	≥ 2000 MΩ*km	
Mutual capacitance	at 800 Hz	Nom. 43 nF/km	
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km	
Mean characteristic impedance	100 MHz	100 ± 5 Ω	
Nominal velocity of propagation		ca. 79 %	
Propagation delay		≤ 427 ns/100m	
Delay skew		≤ 12 ns/100m	
Test voltage	(DC, 1 min) core/core and core/screen	1000 V	
Transfer impedance	bei 1 MHz	≤ 12 mΩ /m	Grade 2
	bei 10 MHz	≤ 10 mΩ /m	
	bei 30 MHz	≤ 30 mΩ /m	
Coupling attenuation		≥ 80 dB	Type 2
Segregation classification acc. EN 50174-2			„D“

Electrical data (nominal)

acc. to Cat.7 (at 20°C)

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ACRF (dB/100m)	PS-ACRF (dB/100m)	Return loss (dB)
1,0	1,8	100	97	98	95	105	105	-
4,0	3,4	100	97	97	94	105	102	27
10,0	5,4	100	97	95	92	97	94	30
16,0	6,8	100	97	93	90	93	90	30
20,0	7,7	100	97	92	89	91	88	30
31,2	9,6	100	97	90	87	87	84	30
62,5	13,7	100	97	86	83	81	78	30
100,0	17,4	100	97	83	80	77	74	30
125,0	19,5	95	92	75	72	75	72	26
155,5	21,9	94	91	72	69	73	70	26
175,0	23,3	93	90	70	67	72	69	25
200,0	25,0	92	89	67	64	71	68	25
250,0	28,1	90	87	62	59	69	66	24
300,0	30,9	89	86	58	55	67	64	24
450,0	38,3	87	84	48	45	64	61	23
600,0	44,8	85	82	40	37	61	58	22
750,0	52,0	83	80	31	28	59	56	21
900,0	59,4	82	79	23	20	58	55	20
1000,0	63,1	80	77	17	14	57	54	20

UC900 HS23 Cat.7

Product order data

Product code	Cable type	Brand name	Outer diameter mm	Euro class	Fire load		Weight kg/km	Copper content	Tensile force N
					MJ/km	kWh/m			
60011263	J-02YSCH 4x2x0.56 PiMF	UC900 HS23 Cat.7 S/FTP 4P LSHF	7.3	E _{ca}	590	0.170	54.5	26	110
60015444	J-02YSCH 2x(4x2x0.56) PiMF	UC900 HS23 Cat.7 S/FTP 2x4P LSHF	7.2/15.0	E _{ca}	1190	0.345	109.2	52	220

Produkt Code Tabelle

Produkt Beschreibung	PG Referenz Code	PG Artikel Nummer
UC900 HS23 C7 S/FTP 4P LSHF	60011263	60011263
UC900 HS23 C7 S/FTP 4P LSHF 50RW	60011263	60015558
UC900 HS23 C7 S/FTP 4P LSHF 100RW	60011263	60011605
UC900 HS23 C7 S/FTP 4P LSHF 250DW	60011263	60015556
UC900 HS23 C7 S/FTP 4P LSHF 500DW	60011263	60011603
UC900 HS23 C7 S/FTP 4P LSHF 500DP	60011263	60013208
UC900 HS23 C7 S/FTP 4P LSHF 1000DW	60011263	60011604
UC900 HS23 C7 S/FTP 2x4P LSHF	60015444	60015444
UC900 HS23 C7 S/FTP 2x4P LSHF 100DW	60015444	60013181
UC900 HS23 C7 S/FTP 2x4P LSHF 500DW	60015444	60013180
UC900 HS23 C7 S/FTP 2x4P LSHF 1000DW	60015444	60015449

© PRYSMIAN GROUP 2013, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.